HOSE - LEGACY HIGH-PRESSURE

For use with hot or cold-water pressure washers.

Introducing the new Legacy hose. The Legacy hose is built to exceed the EN1829-2 Standard and will provide superior abrasion resistance that will increase the life of the hose. The Legacy hose is rated up to 250° F and is available in 4000 and 6000 PSI.

Both single-and double-wire braid hoses come with durable 8" bend restrictors on both ends.

The Legacy hose has a "bite-the-wire" coupling that grips the hose better than any other design.

- Temperature Rating: Legacy hoses are rated for continuous temperatures up to 250° F
- Easily Identified: Permanently embossed identification makes for easy tracing and owner protection.
- Unique Coupling: A "bite-the-wire" coupling actually reaches the wire braid for never-slip retention, far superior to the "compression" fittings used on conventional hoses.

HOSE - 1-WIRE

- Black Bend Restrictor
- Rated to 250° F
- Smooth impression, oil resistant tube and black hose guard at both ends

PART NO.	SIZE	TEMPERATURE	PSI
3/8" MPT Swivel x 3/8" MPT Solid, 3/8" ID			
8.925-176.0	3/8" x 15'	250° F	4000
8.925-150.0	3/8" x 25'	250° F	4000
8.925-156.0	3/8" x 50'	250° F	4000
8.925-161.0	3/8" x 75'	250° F	4000
8.925-165.0	3/8" x 100'	250° F	4000
8.925-170.0	3/8" x 150'	250° F	4000
8.925-350.0	3/8" x 200'	250° F	4000
8.925-378.0	Case of 75 (8.925-156.0) 3/8" x 50' Hoses		
8.925-449.0	Case of 40 (8.925-165.0) 3/8" x 100' Hoses		
3/8" MPT Swivel x 3/8" MPT Swivel, 3/8" ID			
8.925-364.0	3/8" x 50'	250° F	4000
8.925-365.0	3/8" x 75'	250° F	4000
8.925-167.0	3/8" x 100'	250° F	4000
8.925-367.0	3/8" x 150'	250° F	4000
8.925-368.0	3/8" x 200'	250° F	4000
1/2" MPT Swivel x 1/2" MPT Solid			
8.925-236.0	1/2" x 50'	250° F	3000
8.925-237.0	1/2" x 75'	250° F	3000
8.925-238.0	1/2" x 100'	250° F	3000
1/4" MPT Swivel x 1/4" MPT, Solid, 1/4" ID			
8.925-143.0	1/4" x 25'	250° F	3000
8.925-144.0	1/4" x 30'	250° F	3000
8.925-145.0	1/4" x 50'	250° F	3000
8.925-146.0	1/4" x 75'	250° F	3000
8.925-147.0	1/4" x 100'	250° F	3000

HOSE - 2-WIRE

- Red Bend Restrictor
- Rated to 250° F
- Smooth impression, oil resistant tube and red hose guard at both ends

PART NO.	SIZE	TEMPERATURE	PSI
3/8" MPT Swivel x 3/8" MPT Solid, 3/8" ID			
8.928-542.0	3/8" x 15'	250° F	6000
8.925-180.0	3/8" x 25'	250° F	6000
8.925-184.0	3/8" x 50'	250° F	6000
8.925-225.0	3/8" x 75'	250° F	6000
8.925-229.0	3/8" x 100'	250° F	6000
8.925-232.0	3/8" x 150'	250° F	6000
8.925-369.0	3/8" x 200'	250° F	6000
8.925-382.0	Case of 75 (8.925-184.0) 3/8" x 50' Hoses		
8.925-450.0	Case of 40 (8.925-229.0) 3/8" x 100' Hoses		
3/8" MPT Swivel x 3/8" MPT Swivel, 3/8" ID			
8.925-311.0	3/8" x 25'	250° F	6000
8.925-313.0	3/8" x 50'	250° F	6000
8.925-314.0	3/8" x 75'	250° F	6000
8.925-316.0	3/8" x 100'	250° F	6000
8.925-325.0	3/8" x 200'	250° F	6000
1/2" MPT Swivel x 1/2" MPT Solid, 1/2" ID			
8.925-247.0	1/2" x 50'	250° F	5000
8.925-249.0	1/2" x 75'	250° F	5000
8.925-253.0	1/2" x 100'	250° F	5000

Specifications, product descriptions and product availability subject to change without notice.

HOSE - RAWHIDE 1-WIRE

- PSI: 3000
- Temperature: 250°F
- Smooth Non-Marking
- SO / SW Couplers Included

PART NO.	OLD NO.	LENGTH	TEMPERATURE	WORKING PSI	APPROX WT (LBS)
3/8" Smooth Yellow Hose					
8.901-800.0	158980	50' x 3/8" ID	250° F	3000	12.0
8.901-802.0	158985	75' x 3/8" ID	250° F	3000	17.0
8.901-804.0	158990	100' x 3/8" ID	250° F	3000	23.0
8.705-720.0*	158900	Must be purchased in 500 ft reels			
3/8" Smooth Blue Hose					
8.739-148.0	158780	50' x 3/8" ID	250° F	3000	12.0
8.739-149.0	158785	75' x 3/8" ID	250° F	3000	17.0
8.739-150.0	158790	100' x 3/8" ID	250° F	3000	23.0
8.739-369.0	158795	150' x 3/8" ID	250° F	3000	34.0
8.724-371.0	158700	Must be purchased in 500 ft reels			
3/8" Smooth Gray Hose					
8.749-935.0		50' x 3/8" ID	250° F	3000	13.0
8.749-936.0		100' x 3/8" ID	250° F	3000	25.0
8.749-945.0		Must be purchased in 500 ft reels			
1/4" Smooth Blue Hose					
8.901-796.0	158880	50' x 1/4" ID	250° F	3000	8.0
8.901-798.0	158890	100' x 1/4" ID	250° F	3000	16.0
8.705-718.0*	158800	Must be purchased in 500 ft reels			

*500 ft reel, 50 ft incremental lengths (max three pieces)

HOSE - LEGACY RAWHIDE 2-WIRE

- PSI: 4000
- Temperature: 250°F
- 3/8", Smooth, Blue
- SO / SW Couplers Included

PART NO.	OLD NO.	LENGTH	TEMPERATURE	WORKING PSI	APPROX WT (LBS)
3/8" Smooth Blue Hose					
8.739-229.0	154415	50'	250° F	4000	17.0
8.739-231.0	154425	100'	250° F	4000	33.0
8.705-651.0*	154400	Must be purchased in 500 ft reels			

*500 ft reel, 50 ft incremental lengths (max three pieces)

HOSE - SMOOTH COVER

- PSI: 4000
- Temperature: 250°F
- 3/8", Wrapped, Grey

PART NO.	LENGTH	DESCRIPTION	TEMPERATURE	PSI
3/8" Smooth Cover, Grey Hose				
8.921-617.0	3/8" x 25'	4K Gray A+ SOXSW	250° F	4,000
8.921-618.0	3/8" x 50'	4K Gray A+ SOXSW	250° F	4,000
8.921-619.0	3/8" x 75'	4K Gray A+ SOXSW	250° F	4,000
8.921-620.0	3/8" x 100'	4K Gray A+ SOXSW	250° F	4,000
8.752-156.0	3/8" Bulk, 4K Gray - Must be purchased in 600 ft reels		250° F	4,000

Specifications, product descriptions and product availability subject to change without notice.

HOSE - LEGACY HOSES WITH COUPLING AND PLUG

- PSI: 4000 - 6000
- Temperature: 0˚F
- Couplers and Plug Included

PART NO.	LENGTH	TEMPERATURE	WORKING PSI	APPROX WT (LBS)
3/8" Black Hose, R1				
8.928-928.0	50' x 3/8" ID	0º F	4000	?
8.928-929.0	100' x 3/8" ID	0º F	4000	?
3/8" Black Hose, R2				
8.928-930.0	50' x 3/8" ID	0º F	6000	?
8.928-931.0	100' x 3/8" ID	0º F	6000	?

HOSE - A+ HOSES WITH COUPLING AND PLUG

- PSI: 4000
- Temperature: 0˚F
- Couplers and Plug Included

PART NO.	LENGTH	TEMPERATURE	WORKING PSI	APPROX WT (LBS)
3/8" Blue Hose				
8.928-971.0	50' x 3/8" ID	0º F	4000	?
8.928-972.0	100' x 3/8" ID	0º F	4000	?
8.928-975.0	50' x 3/8" ID	0º F	4000	?
8.928-974.0	100' x 3/8" ID	0º F	4000	?

HOSE - TUFF-FLEX - 2-WIRE

- PSI: 6000
- 3/8, Blue
- Temperature: 250˚F
- Non-Marking Durable Blue Cover
- Red Hose Guard
- 50% Greater Flexibility
- 3/8" MPT Swivel x 3/8" MPT Solid
- Smooth impression, maximum oil-resistant tube and cover

PART NO.	LENGTH	TEMPERATURE	WORKING PSI
3/8" Tuff-Flex 2-Wire Blue Hose			
8.921-153.0	25' x 3/8" ID	250º F	6000
8.921-154.0	50' x 3/8" ID	250º F	6000
8.921-155.0	75' x 3/8" ID	250º F	6000
8.921-156.0	100' x 3/8" ID	250º F	6000
8.753-319.0	Must be purchased in 600 ft reels		

Specifications, product descriptions and product availability subject to change without notice.

HOSE - TUFF -FLEX - 1-WIRE

- PSI: 4000
- 3/8, Blue
- Temperature: 250°F
- Non-Marking Durable Blue Cover
- Red Hose Guard
- 50% Greater Flexibility
- 3/8" MPT Swivel x 3/8" MPT Solid
- Smooth impression, maximum oil-resistant tube and cover

PART NO.	LENGTH	TEMPERATURE	WORKING PSI
3/8" Tuff-Flex 1-Wire Blue Hose			
8.921-149.0	25' x 3/8" ID	250° F	4000
8.921-150.0	50' x 3/8" ID	250° F	4000
8.921-151.0	75' x 3/8" ID	250° F	4000
8.921-152.0	100' x 3/8" ID	250° F	4000
8.753-316.0	Must be purchased in 600 ft reels		

PRESSURE LOOP - 2-WIRE

The 1/4" ID pressure lines solid / swivel for most any application. The 3/8" ID pressure loops have female JIC on both ends for typical unloader connection hose. All pressure loops are rated for 275° F.

- 1/4" ID Pressure Loop
- 1/4" MPT Swivel x 1/4" MPT Solid
- 1/4" ID Two-Wire, 5000 PSI
- Any Length Available

- JIC Pressure Loop
- 1/2" Female JIC Swivels - Each End
- 3/8" ID Two-Wire, 6000 PSI
- 1/2" ID 4500 PSI
- Any Length Available

PART NO.	OLD NO.	LENGTH	TEMPERATURE	PSI
1/4" Pressure Loop				
8.918-180.0		16" x 1/4" ID	250° F	6000
8.918-181.0		20" x 1/4" ID	250° F	6000
8.918-182.0		26" x 1/4" ID	250° F	6000
8.918-183.0		28" x 1/4" ID	250° F	6000
8.918-184.0		30" x 1/4" ID	250° F	6000
8.918-419.0		36" x 1/4" ID	250° F	6000
8.918-187.0		42" x 1/4" ID	250° F	6000
3/8" JIC Pressure Loop				
8.918-210.0		16" x 3/8" ID	250° F	6000
8.918-422.0		20" x 3/8" ID	250° F	6000
8.918-423.0		22" x 3/8" ID	250° F	6000
8.918-424.0		25" x 3/8" ID	250° F	6000
8.918-425.0		29" x 3/8" ID	250° F	6000
8.918-426.0		32" x 3/8" ID	250° F	6000
8.918-427.0		36" x 3/8" ID	250° F	6000
8.711-662.0	4-02047738	38" x 3/8" ID	250° F	6000
8.918-212.0		42" x 3/8" ID	250° F	6000
1/2" JIC Pressure Loop				
8.918-224.0		20" x 1/2" ID	275° F	4500
8.711-701.0	4-02067722	22" x 1/2" ID	275° F	4500
8.918-225.0		28" x 1/2" ID	275° F	4500
8.918-228.0		46" x 1/2" ID	275° F	4500
8.918-230.0		70" x 1/2" ID	275° F	4500

HOSE - WHITEWATER® COMBINATION STEAM HOSE

Good up to 3000 PSI - 250° F or 350 PSI - 325° F

- Single High-Tensile Steel Wire Braid
- High Temperature Bend Restrictors - Both Ends
- Seamless Innertube
- Solid 3/8" or 1/2" MPT Connectors - Both Ends (Swivel Ends NOT Available)
- Oil-Resistant Cover

PART NO.	OLD NO.	LENGTH	TEMPERATURE	WORKING PSI
3/8" Steam Hose				
8.901-559.0	153930	30'	325° F	3000
8.901-601.0	153950	50'	325° F	3000
8.901-598.0	153925	25'	325° F	3000
8.901-603.0	153975	75'	325° F	3000
8.901-604.0	153990	100'	325° F	3000
8.705-643.0	153900*	Must be purchased in 500 ft reels		
1/2" Steam Hose				
8.901-721.0	155625	25'	325° F	2500
8.901-723.0	155650	50'	325° F	2500
8.901-724.0	155675	75'	325° F	2500
8.901-725.0	155690	100'	325° F	2500
8.705-678.0	155600*	Must be purchased in 500 ft reels		

*Full Reel - 500 ft per reeel, hose only, 50 ft incremental lengths (max three pieces)

PULSE HOSE

- PSI Working Pressure: 1300
- 3/8" MPT On Both Styles
- Available with either plug-end or open-flow with solid / swivel connects

PART NO.	OLD NO.	LENGTH	DESCRIPTON	WORKING PSI
8.711-151.0	381118	18"	w/ Plug End	1300
8.711-153.0	381124	24"	w/ Plug End	1300
8.711-155.0	381128	28"	Solid / Swivel - Open	1300
8.711-157.0	381136	36"	Solid / Swivel - Open	1300

HOBBY HOSE

Replacement hose for most hobby pressure washers sold by mass retailers.

- PSI Working Pressure: 2250
- PSI Burst Pressure: 9000
- Thermoplastic Cover
- Fiber-braid Reinforcement
- M22 x 1.5 Fitting Inlet
- 14 mm Seal Cone Fits Generac, Excell and Kärcher
- 15 mm Seal Cone Fits Campbell, MI-T-M

PART NO.	OLD NO.	LENGTH	SEAL CONE	ID
8.705-485.0	150245	25'	14mm	1/4"
8.705-487.0	150246	25'	15mm	1/4"
8.753-423.0	4-02010025M	25'	22mm*	1/4"

HOSE BEND RESTRICTORS

- Temperature: 325° F
- Used on Hose Assemblies
- Non-Slip Sure Fit
- Easy Installation
- Top-Quality Molded Fit Bend Restrictors
- Fits snugly to prevent kinks near the connectors

PART NO.	OLD NO.	LENGTH	TEMPERATURE	COLOR
1 Wire				
8.705-479.0	150166	5.3' x 1/4"	325° F	Black Vinyl
8.705-476.0	150161	6.0" x 1/2"	325° F	Black Vinyl
8.740-104.0		24.0" x 3/8"	325° F	Black Vinyl
8.756-784.0	150170	8.0" x 1/2"	325° F	Black Vinyl
2 Wire				
8.756-735.0		1/2" x 8"	325° F	Red Vinyl
8.705-478.0	150164	6.0" x 3/8"	325° F	Red Vinyl
8.711-846.0		24.0" x 3/8"	325° F	Red Vinyl
8.705-480.0	150168	7.0" x 3/8"	325° F	Red Vinyl
Combo				
8.705-483.0	150174	6.5" x 3/8" ID	325° F	Gray Vinyl
8.705-482.0*	150172	6.5" x 1/2" ID	325° F	Black Rubber
*Insulated rubber				

GARDEN HOSE - APEX QUALITY

The essential product for pressure washing

- Rated For Cold-Water User
- Assemblies Complete With Bend Restrictor
- 5/8" or Larger ID For Full Flow
- Choice of Commercial or Heavy-Duty Grade
- Reninforced hose for flexiability and strength in all weather
- Commercial grade has machined octago-I "wrench tight" fittings

PART NO.	OLD NO.	LENGTH	GRADE	COLOR
8.704-786.0	121315	50' x 5/8" ID	Com	Gray
8.704-787.0	121319	100' x 5/8" ID	Com	Gray
8.704-788.0	121332	50' x 5/8" ID	HD	Light Green
8.704-789.0	121336	100' x 5/8" ID	HD	Light Green
All Rubber Reinforced Hot Water Hose - 160° F				
8.704-790.0	121344	50' x 5/8" ID	Com	Red
8.704-791.0	121348	50' x 3/4" ID	Com	Red

See page 28 for garden hose fittings

SEWER HOSE

Super flexible sewer line hose and couplings have small outside diameter, allowing hose and nozzles to fit through sewer line. Sewer line has super-tough poly-ether cover over ultra-flexible nylon tube. 1/8" sewer nozzle and hose will operate through many 1-12" lines.

- Max Temperature: 160° F
- 1.5 GPM Optimum Flow 1/8"
- 2.5 GPM Optimum Flow 1/4"
- Nylon Tube, Polyether Cover

Nozzles Not Included

PART NO.	OLD NO.	LENGTH	TEMPERATURE	GPM	PSI
1/8" Hose - 1/4" Inlet, 1/8" Outlet					
8.751-927.0	150960	1/8" x 25'	160° F	1.5	4800
8.705-602.0	150963	1/8" x 50'	160° F	1.5	4800
8.705-603.0	150964	1/8" x 100'	160° F	1.5	4800
1/4" Hose - 1/4" Inlet, 1/4" Outlet					
8.705-607.0	150968	1/4" x 50'	160° F	2.5	2600
8.705-608.0	150970	1/4" x 100'	160° F	2.5	2600
1/4" Hose - 1/4" Inlet, 1/4" Outlet					
8.705-610.0	150972	1/4" x 50'	160° F	2.5	4400
8.705-611.0	150973	1/4" x 100'	160° F	2.5	4400

Specifications, product descriptions and product availability subject to change without notice.

ORANGE 600 SPRAYER HOSE AND RIBBED PVC SPRAYER HOSE

Braid-reinforced PVC hose designed specifically for AG / Pest control spraying applications.

- Max PSI: 600
- Color: Orange
- Tough Ribbed Cover
- Bulk hose standard in 300' single length coils
- Resists Abrasion and UV Rays

PART NO.	OLD NO.	LENGTH	PSI
3/8" Hose - Orange			
8.705-527.0	150630	300' Coil, Single, Uncut Length	600
8.901-384.0	150634	50' Bulk	600
8.901-385.0	150636	100' Bulk	600
8.901-383.0	150632	Per Foot - 25' Minimum Hose Only	600
1/2" Hose - Orange			
8.705-523.0	150601	300' Coil, Single Uncut Length	600
8.901-377.0	150603	50' Bulk	600
8.901-379.0	150606	100' Bulk	600
8.705-524.0	150602	Per Foot - 25' Hose Only	600
3/4" Hose - Orange			
8.705-531.0	150660	1/4" x 50'	600
8.901-386.0	150660	1/4" x 100'	600

COLD WEATHER GARDEN HOSE

- Ideal for outdoor contractors
- 5/8" - 50 ft
- High-Quality Brass Fittings
- Heated Hose with 110 Plug
- Thermostatically controlled - heating element is activated at +/- 35° F temperature and turned off at +/- 40° F ambient temperature
- Use only with a UL approved GFCI outlet or extension
- PVC material FDA-approved for potable water

PART NO.	LENGTH	DESCRIPTION
8.749-944.0	5/8" x 50'	Cold Weather Garden Hose

See page 28 for garden hose fittings

VINYL TUBING

This 1/4" x 1/2" clear vinyl tubing is heavier duty than the rest! Thick wall resists kinking. Available in clear or clear-reinforced with polyster braid.

- Very Flexible
- Available by the foot or 100' rolls

PART NO.	OLD NO.	LENGTH	PSI	DESCRIPTION
9.802-251.0	4-02080000	1/4" x 1/2"	50	Clear Vinyl
9.802-252.0	4-02090000	1/4" x 1/2"	250	Braided Vinyl
8.711-733.0		3/8" x 1/2"	100	Sold by the foot

CLEAR REINFORCED PVC TUBING

Multi-use, industrial-grade tubing with high-resistance to chemicals, solvents and fuel.

- Reinforced With Polyester Cord
- Huge Selection of Sizes and Lengths
- 4-to-1 Burst Safety Factor

PART NO.	OLD NO.	ID X OD	WP AT 70° F	ROLL LENGTH
8.901-256.0	121031	1/4" x 3/8"	250	25'
8.901-257.0	121032	1/4" x 3/8"	250	50'
8.704-751.0	121033	1/4" x 3/8"	250	100'
8.704-752.0	121034	1/4" x 3/8"	250	300'
8.901-260.0	121036	3/8" x 1/2"	175	25'
8.901-261.0	121037	3/8" x 1/2"	175	50'
8.901-262.0	121038	3/8" x 1/2"	175	100'
8.704-753.0	121039	3/8" x 1/2"	175	300'
8.901-264.0	121041	1/2" x 3/4"	175	25'
8.901-265.0	121042	1/2" x 3/4"	175	50'
8.704-754.0	121043	1/2" x 3/4"	175	100'
8.704-755.0	121044	1/2" x 3/4"	175	300'
8.901-263.0		1/2"	175	per ft
8.901-267.0	121046	5/8" x 7/8"	175	25'
8.901-268.0	121047	5/8" x 7/8"	140	50'
8.901-269.0	121048	5/8" x 7/8"	140	100'
8.704-756.0	121049	5/8" x 7/8"	140	300'
8.901-266.0		5/8"	140	per ft
8.901-271.0	121051	3/4" x 1"	140	25'
8.901-272.0	121052	3/4" x 1"	140	50'
8.704-757.0	121053	3/4" x 1"	140	100'
8.704-758.0	121054	3/4" x 1"	140	300'
8.901-270.0		3/4"	140	per ft
8.901-273.0	121059	1" x 1 1/4"	75	25'
8.901-274.0	121060	1' x 1 1/4"	75	50'
8.901-275.0	121061	1" x 1 1/4"	75	100'
8.704-759.0	121063	1" x 1 1/4"	75	200'
8.901-276.0		1"	75	per ft

See page 28 for hose clamps

CRIMP FITTINGS

PART NO.	SIZE	HOSE
8.724-027.0	3/8" MPT, Solid	3/8"
8.724-028.0	3/8" MPT, Swivel	3/8"
8.724-029.0	1/2" FJIC, Solid	3/8"
8.706-759.0	3/8" FPT, Swivel	3/8"

Specifications, product descriptions and product availability subject to change without notice.

FIELD ATTACHABLE COUPLINGS

Designed and build your own hose or adapt and repair hose in the field (no crimper required).

PART NO.	OLD NO.	ID X MPT
1-Wire Braid Hose Couplings		
8.705-493.0	150502	1/4" x 1/4", Solid
8.705-495.0	150505	1/4" x 1/4", Swivel
8.705-496.0	150510	3/8" x 1/4", Solid
8.705-497.0	150511	3/8" x 3/8", Solid
8.705-498.0	150513	3/8" x 3/8", Swivel
8.705-499.0	150515	1/2" x 3/8", Solid
8.705-500.0	150516	1/2" x 1/2", Solid
8.705-501.0	150518	1/2" x 1/2", Swivel
2-Wire Braid Hose Couplings		
8.705-502.0	150532	1/4" x 1/4", Solid
8.705-503.0	150535	1/4" x 1/4", Swivel
8.705-505.0	150541	3/8" x 3/8", Solid
8.705-506.0	150543	3/8" x 3/8", Swivel
8.705-507.0	150546	1/2" x 1/2", Solid
8.705-508.0	150548	1/2" x 1/2", Swivel

CLEAR PVC TUBING

- "Box Pak" 100 ft
- Temperature: 25° F to 150° F
- Very Flexible, Non-Reinforced
- Packaged in self-dispensing box

PART NO.	ID X OD	WP AT 70° F
8.901-279.0	1/4" x 3/8"	55
8.704-766.0	1/2" x 5/8"	30

CONNECTOR HOSE - 2' - 10'

Connector hose comes with one solid - one swivel end.

PART NO.	LENGTH	PSI	HOSE COLOR
3/8" Ultima - 2-Wire - W/O Bend Restrictors			
8.918-271.0	2'	6000	Black
8.918-273.0	3'	6000	Black
8.918-276.0	4'	6000	Black
8.918-278.0	5'	6000	Black
8.918-280.0	6'	6000	Black
8.918-282.0	7'	6000	Black
8.918-284.0	8'	6000	Black
8.918-420.0	9'	6000	Black
8.918-288.0	10'	6000	Black
3/8" Ultima - 2-Wire - W/ Bend Restrictors			
8.918-272.0	2'	6000	Black
8.918-275.0	3'	6000	Black
8.918-277.0	4'	6000	Black
8.918-209.0	5'	6000	Black
8.918-281.0	6'	6000	Black
8.918-283.0	7'	6000	Black
8.918-285.0	8'	6000	Black
8.918-287.0	9'	6000	Black
8.918-289.0	10'	6000	Black
1/2" Ultima - 2-Wire - W/O Bend Restrictors			
8.918-292.0	2'	5000	Black
8.918-294.0	3'	5000	Black
8.918-296.0	4'	5000	Black
8.918-298.0	5'	5000	Black
8.918-300.0	6'	5000	Black
8.918-301.0	7'	5000	Black
8.918-302.0	8'	5000	Black
8.918-303.0	9'	5000	Black
8.918-304.0	10'	5000	Black

FLEX LINE BYPASS / SUPPLY LINE HOSE

Industrial PVC hose with black seamless inner tube, polyester braid reinforced tough outer cover. Excellent for use as supply lines or bypass lines. Typically used for air hose.

- Looks and Feels Like Rubber
- Smooth Dirt and Oil Resistant Finish
- Super Flexible
- Abrasion-Resistant Cover
- Burst-Rated Three-Times WP

PART NO.	OLD NO.	ID X OD	WP AT 70° F	ROLL LENGTH
Red Cover, Heavy Wall				
8.901-281.0	21081	3/8" x .634"	300	50'
8.704-762.0	121084	3/8" x .634"	300	500'
8.901-282.0	121087	1/2" x .792"	250	50'
8.704-764.0	121090	1/2" x .792"	250	500'
8.901-284.0	121097	3/4" x 1.14"	160	50'
8.704-765.0	121099	3/4" x 1.14"	160	300'
Blue Cover, Standard Wall				
8.704-779.0	121160	1/4" x .475"	250	100'

Specifications, product descriptions and product availability subject to change without notice.

CONNECTOR HOSE - 2' - 10'

Connector hose comes with one solid - one swivel end.

PART NO.	LENGTH	PSI	HOSE COLOR
3/8" Ultima - 1-Wire W/O Bend Restrictors			
8.918-253.0	2'	4000	Black
8.918-255.0	3'	4000	Black
8.918-257.0	4'	4000	Black
8.918-259.0	5'	4000	Black
8.919-261.0	6'	4000	Black
8.918-263.0	7'	4000	Black
8.918-265.0	8'	4000	Black
8.918-267.0	9'	4000	Black
8.918-269.0	10'	4000	Black

PART NO.	LENGTH	PSI	HOSE COLOR
1/4" Ultima - 1-Wire W/O Bend Restrictorss			
8.918-240.0	2'	4000	Black
8.918-241.0	3'	4000	Black
8.918-242.0	4'	4000	Black
8.918-243.0	5'	4000	Black
8.918-245.0	6'	4000	Black

CONNECTOR HOSE - CAR WASH BAY HOSE - 12' - 25'

All car wash bay hoses come with solid male pipe on both ends.

PART NO.	LENGTH	PSI
3/8" Ultima - 1-Wire W/O Bend Restrictors		
8.918-333.0	12'	4000
8.918-334.0	13'	4000
8.918-336.0	14'	4000
8.918-338.0	15'	4000
8.918-340.0	16'	4000
8.918-342.0	17'	4000
8.918-344.0	18'	4000
8.918-348.0	20'	4000
3/8" Ultima - 1-Wire W/ Bend Restrictors One End		
8.919-123.0	12'	4000
8.918-335.0	13'	4000
8.918-337.0	14'	4000
8.918-339.0	15'	4000
8.918-349.0	20'	4000
1/4" Blue - 1-Wire W/O Bend Restrictors		
8.918-389.0	13'	3000
8.918-391.0	14'	3000
8.918-393.0	15'	3000
8.918-395.0	16'	3000
8.918-397.0	17'	3000
8.918-399.0	18'	3000
8.918-401.0	19'	3000
8.918-403.0	20'	3000
8.918-409.0	23'	3000
8.918-411.0	24'	3000
8.918-413.0	25'	3000

PART NO.	LENGTH	PSI
3/8" Blue - 1-Wire W/O Bend Restrictors		
8.918-360.0	12'	3000
8.918-366.0	15'	3000
8.919-124.0	16'	3000
8.918-369.0	17'	3000
8.918-371.0	18'	3000
8.918-375.0	20'	3000
3/8" Blue - 1-Wire W/ Bend Restrictors One End		
8.918-367.0	15'	3000
8.918-368.0	16'	3000
8.918-372.0	18'	3000
8.918-376.0	20'	3000
1/4" Blue - 1-Wire W/ Bend Restrictors One End		
8.918-388.0	12'	3000
8.918-390.0	13'	3000
8.918-392.0	14'	3000
8.918-404.0	20'	3000

Specifications, product descriptions and product availability subject to change without notice.

LEGACY STACKABLE HOSE REELS

Hose reels built specifically for contractors who require flexibility on a job site. Stackable reels are supported on both sides of the central hub to accomodate more aggressive applications, such as trailer-mounted.

200' Mild Steel Stackable Hose Reel

100' Mild Steel Stackable Hose Reel

- Integrated frame adds protection and stacking ability
- Stacked up to 3 high
- Heavy-duty powder-coated steel or stainless steel
- Reel and swivel rated up to 6000 PSI and 350° F
- Modular design is able to configure for various needs
- Reversible hand-crank and swivel

PART NO.	DESCRIPTION
9.801-767.0	Stackable Hose Reel, Mild Steel, 100'
9.801-768.0	Stackable Hose Reel, Mild Steel, 200'
9.801-769.0	Stackable Hose Reel, Stainless-steel, 100'
9.801-770.0	Stackable Hose Reel, Stainless-steel, 200'
NOTE: Hose not included	
8.923-415.0	Hose Guide, 100' Reel
8.923-427.0	Hose Guide, 200' Reel
8.923-416.0	Hose Reel Riser
8.923-918.0	Reel Cart System

Stainless-Steel Stackable Hose Reel

200' Mild Steel Stackable Hose Reel with Optional Hose Guide and Hose Reel Riser

200' Mild Steel Stackable Hose Reel with Optional Reel Cart System and Hose Guide

Options

Reel Cart System

Hose Reel Riser

Hose Guide

Specifications, product descriptions and product availability subject to change without notice.

LEGACY HOSE REELS

Legacy hose reels were designed for ease of use and durability in commercial pressure washer applications. Offering 100' and 200' reels in both a fixed base and 360 degree rotating base. The oversized reel holds the advertised length plus leaves additional space reducing the difficulty of reeling hose. The unique extended swivel improves the hose connection and reduces hose wear and stress.

Fixed Base Hose Reel

360° Pivot Reel

- PSI: 5000
- Temperature: 325° F
- 100' - 200' Fixed Base
- 100' - 200', 360° Rotating Base
- High-Pressure, Double-Seal Swivels
- Reels equipped for 3/8" hose. Easily convertible to 1/2" hose with the change to a 1/2" swivel
- 2-Year Warranty

Bracket Sockets

Universal Mount

Skid Mount

Wall Mount

Base Mount

Non-Pivot Reel Brackets

Universal

90°

45°

Vertical

PART NO.	DESCRIPTION
8.750-485.0	Pivot Reel, 100' x 3/8", Hose Not Included
8.750-482.0	Pivot Reel, 200' x 3/8", Hose Not Included
8.750-476.0	Fixed Based, 100' x 3/8", Hose Not Included
8.750-479.0	Fixed Based, 200' x 3/8", Hose Not Included
8.919-430.0	Universal Mount
8.919-794.0	Skid Mount
8.919-437.0	Wall Mount
8.919-434.0	Base Mount
8.919-072.0	Bracket, Universal
8.919-445.0	Bracket, 90°
8.919-441.0	Bracket, 45°
8.919-448.0	Bracket, Vertical

LEGACY HOSE REEL SWIVELS

- PSI: 5000
- Innovative Design
- Stainless-Steel Rotor
- Unique Dual Seal for Extra Long Life
- 2-Year Warranty

PART NO.	INLET X OUTLET
Swivel	
9.118-021.0	1/2" x 3/8" F
8.776-003.0	1/2" F x 3/8" F
9.118-023.0	3/8" M x 3/8" F
9.118-024.0	3/8" F x 3/8" F
9.118-025.0	1/2" M x 1/2" F
9.118-026.0	1/2" x 1/2" F
9.118-027.0	3/8" M x 1/2" F
9.118-028.0	3/8" F x 1/2" F
Universal Repair Kit	
8.776-001.0	

- PSI: 5000
- Limits Bend and Hose Stress
- Stainless-Steel Rotor
- Unique Dual Seal for Extra Long Life
- 2-Year Warranty

PART NO.	INLET X OUTLET
Extended Swivels	
9.118-020.0	1/2" M x 3/8" F
9.118-029.0	1/2" F x 3/8" F
9.118-030.0	3/8" M x 3/8" F
9.118-031.0	3/8" F x 3/8" F
9.188-034.0	1/2" F x 1/2" F
9.118-035.0	1/2" M x 1/2" F
9.118-032.0	3/8" F x 1/2" F
9.118-033.0	3/8" M x 1/2" F
Universal Repair Kit	
8.776-001.0	

Specifications, product descriptions and product availability subject to change without notice.

AP HOSE REELS

AP hose reels have been designed to perfectly balance ruggedness and durability with affordability.

- Working PSI: 4000
- Rated Temperature: 225° F
- 3/8" or 1/2" Inlet / Outlet
- Flared Flanges for Maximum Capacity
- Solid Center Core for Maximum Strength
- Rolled, Beaded-Edge Flanges for Maximum Safety
- Easy Mounting Options for Maximum Versatility
- "Posi-Pin" Lock Prevents Unwanted Dereeling
- Heavy-Duty Powder-Coated Steel
- Easy Access External Swivel

PART NO.	OLD NO.	HOSE DIAMETER	CAPACITY (FT)	CORE WIDTH	FLANGE WIDTH	FLANGE DIAMETER	OVERALL HEIGHT
8.711-192.0	386188	3/8"	50	4.3	7.9	10.5	13"
9.804-067.0	386191	3/8"	100	8.7	12.2	10.5	13"
8.711-199.0	386206	3/8"	150	6.3	10.2	13.0	16.7"
8.711-201.0	386209	1/2"	100	6.3	10.2	13.0	16.7"
8.712-460.0	421043	Replacement Swivel for Part No. 8.711-192.0 and 9.804-067.0					
8.712-469.0	421063	Replacement Swivel for Part No. 8.711-199.0					
8.754-280.0	421045	Replacement Swivel for Part No. 8.711-201.0					
8.700-188.0	4-0203612	Replacement Handle					
Swivel Repair Kits							
8.900-855.0	110025						

Note: Hose is not included. See page 140 for connector hose.

- Working PSI: 4000
- Rated Temperature: 225° F
- Super-Reinforced Core - Won't Collapse!
- Adjustable Brake for Controlled Reel Tension
- Convenient External Swivel
- Manual Rewind Handle Included
- Solid Core Bolts on to Flanges for Extra Strength
- Snap-Lock to Prevent Accidental Dereeling
- Bearings Have Oil Cap for Easy Field Maintenance

PART NO.	OLD NO.	HOSE DIAMETER	CAPACITY (FT)	REEL SIZE WIDTH	REEL SIZE DIAMETER
8.711-182.0	386174	3/8"	150	6"	18"
8.711-183.0	386175	3/8"	300	10"	18"
8.711-184.0	386176	3/8"	350	14"	18"
8.711-189.0	386181	1/2"	200	10"	18"
8.711-190.0	386182	1/2"	270	14"	18"
8.715-921.0	600975T	Replacement Brake for Part No. 8.711-182.0 and 8.711-183.0			

NOTE: Hose is not included. Interchangeable parts available. Call for pricing. See page 140 for connector hose.

PART NO.	OLD NO.	HOSE DIAMETER	CAPACITY (FT)	REEL SIZE WIDTH	REEL SIZE DIAMETER
8.711-179.0	386171	3/8"	90	6"	14"
8.711-180.0	386172	3/8"	140	10"	14"
8.711-181.0	386173	3/8"	200	14"	14"
8.711-186.0	386178	1/2"	115	10"	14"
8.711-187.0	386179	1/2"	150	14"	14"

NOTE: Hose is not included. Interchangeable parts available. Call for pricing. See page 140 for connector hose.

PART NO.	OLD NO.	HOSE DIAMETER	DESCRIPTION
8.700-287.0	075130	3/8"	Swivel Repair Kit
8.700-285.0	075128	1/2"	Swivel Repair Kit
8.900-855.0*	110025		Swivel Repair Kit

*For Round Swivels. Replacement Swivels, See Page 24

Specifications, product descriptions and product availability subject to change without notice.

COXREELS HOSE REELS

Coxreels offer high performance in a very compact and lightweight hand crank or spring-driven hose reel. Perfect for mobile application and permanent floor and wall mount.

8.711-858.0

- Rated Up to 4000 PSI
- Temperature: -20° F to 225° F
- Adjustable Drag Brake
- 90° Brass Swivel

9.802-265.0

- Spring Driven Hose Reel
- Lightweight, Compact Design
- Adjustable Drag Break
- Sturdy U-Shaped Frame
- PSI: Up To 4000
- Rolled edges and ribbed dics provide strength and safety
- Pro-Grade Heavy-Duty Steel
- 2-Year Mfg Limited Warranty

8.723-649.0
(Hose and Ball Stop Not Included

PART NO.	OLD NO.	PSI	DESCRIPTION
8.711-858.0	4-0275001	3000	200' x 1/2" (300' x 3/8" w/ Adapter
8.711-860.0	4-02750002	4000	100' x 3/8"
9.802-265.0	4-02750003	4000	150' x 3/8"
8.711-591.0	4-020369		Handle Replacement
8.711-588.0	4-020366		Locking Pin Assembly
8.723-649.0	87236490	4000	50' x 3/8" Spring Driven
8.705-132.0	140407		1/2" to 3/8" Adapter for 8.711-858.0
8.750-020.0			Ball Stop for 8.723-649.0
8.711-584.0	4-020362		Replacement Swivel, 1/2"
8.711-585.0	4-020363		Replacement Swivel, 3/8"

Specifications, product descriptions and product availability subject to change without notice.